


A-A (1 : 1)



CODE	SIZE	G	L	L1	SW	SW1	O-RING
230OR 38	3/8	3/8	41,5	9	21	24	12,42x1,78
230OR 12	1/2	1/2	46,5	11	25	30	15,60x1,78
230OR 34	3/4	3/4	51	12,5	31	37	22,22X2,62
230OR 01	1"	1"	61	14,5	38	OT.46	28,25x2,62
230OR P4	1"1/4	1"1/4	69	15	OT.48	OT.52	36,17x2,62
230OR P2	1"1/2	1"1/2	71	17	OT.54	OT.64	45,69x2,62
230OR 02	2"	2"	82,5	17	OT.67	OT.71,5	51,94x3,53

CONFORMITY	
1) DM 174 del 6 Aprile 2004	
2) UNI EN ISO 228	
3)UNI EN 1254-4	

WORKING PRESSURE MAX	10 BAR
WORKING TEMPERATURE MAX	80°C

00	Prima emissione	Delaini M.	11/02/2008
Rev.	Nota Revisione	Approvatore	Data Approvazione
Toll Gen:	JS13	Stato sup.:	Giallo Sabbiato
Filetto:	ISO 228	Note tecniche:	
Peso lavorato:	Peso grezzo:	N° stampo:	
Materiale:		Disegnatore:	Data:08/02/2008
		Delaini P.	
TDM Brass s.r.l via Artigiani , 7-9 25030 Maclodio BS Italy tel +39 030 9972217 fax 030 9787089 www.tdmbrass.it email info@tdmbrass.it		TDM BRASS <i>Italian Fittings</i>	

Codice: 230OR scheda

Descrizione: 3 piece connector M/F with o-ring